

Stylesheet Version 1.0

Background of Invention

[0002] This invention relates to fuel tanks, and more particularly to a relatively lightweight structure for containing fuel that protects against fuel leakage and has fire protection qualities.

[0004] Large generators are self contained sources of power that run on liquid fuel to provide auxiliary power. The tank that provides a reservoir of fuel for the motor is an integral part of the generator. Generators are required to provide uninterrupted power for extended periods of time without refueling.

Page 1 of 15

confirmed releases of hazardous substances into the environment by USTs.

[0006] Aboveground storage tanks are being used more frequently to address the problems of environmental contamination from leaking underground storage tanks. The aboveground fuel tanks are shop fabricated, inspected and tested for leakage prior to installation. Aboveground storage tanks designated as "generator base tanks" are designed to serve as a support means and base for a generator. Generator base tanks are built with a dual tank configuration where an inner primary tank is encased by an outer integral secondary tank. The dual tank construction is intended to limit the heat transferred to the primary tank and also to prevent any leakage from the primary tank from entering the environment. Underwriters Laboratory Inc. (UL) standard 2085 is associated with the safety for protected aboveground tanks for flammable and combustible liquids. UL 2085 provides the requirements that cover shop fabricated, aboveground atmospheric protected tanks intended for the storage of stable, flammable, or combustible liquids that have a specific gravity not greater than 1.0 and that are compatible with the material and construction of the tank. Tank constructions that meet UL 2085 will limit the heat transferred to the primary tank when exposed to a two-hour hydrocarbon pool fire and provide protection from physical damage.

[0007] Concrete between the inner primary tank and the outer secondary tank provides fire protection for the stored fuels. By way of example, U.S. Patent Nos. 5,695,089 and 5,809,650 to Reese et al. use porous concrete as an insulator. The concrete works well as a fire shield, however, the concrete also makes the tank extremely heavy and cumbersome to transport and install.

[0008] U.S. Patent No. 3,875,886 to Glasfeld et al. describes an insulating layer comprising foamed plastic material in combination with a thin, solid barrier layer or liner applied thereto. However, the Glasfeld patent is directed to cryogenic fluid storage and accordingly addresses problems of extreme cold and ductility in conventional steel tanks. Conversely, the instant invention relates more specifically to fire hazards.

Sub B [0009] ~~United States Patent No. 3,787,279 to Winchester describes a fuel tank for~~

storage systems.

[0015] Accordingly, what is needed in the art is a fire resistant fuel tank which meets all applicable fire requirement standards and is concomitantly relatively lightweight and is easy to install. It is, therefore, to the effective resolution of the aforementioned problems and shortcomings of the prior art that the present invention is directed.

[0016] However, in view of the prior art in at the time the present invention was made, it was not obvious to those of ordinary skill in the pertinent art how the identified needs could be fulfilled.

Summary of Invention

[0017] The present invention is an aboveground storage tank for flammable and combustible liquids having secondary containment capability, comprising an inner primary tank for storing the liquid, an outer secondary tank encasing the inner primary tank defining a substantially uniform interstitial space therebetween, an insulating foam material disposed of in the substantially uniform interstitial space, and a fire resistant textile material sandwiched between the foam material and the outer secondary tank so that a fire resistant composite comprised of insulating foam and fire resistant textile material encases the inner primary tank.

[0018] The insulating foam material located in the interstitial area between the primary inner tank and the secondary outer tank can be polystyrene, urethanes, polymethyl methacrylate, or a variety of other polymers. For most embodiments and applications of the present invention, the foam material is preferably a synthetic polymer or rubber. The fire resistant textile material can be a high-temperature polyester film material such as Mylar or Kevlar.

[0019] It is therefore an object of the present invention to provide a relatively lightweight generator base tank.

[0020] It is another object of the present invention to provide a generator base tank that meets or exceeds all applicable fire resistant standards.

0062168-073401
TOFE2032500

SubB3

to the fuel in the tank 10 and thus reduce the vapor pressure buildup in inner tank volume 120.

[0031] A secondary emergency vent 90 provides an escape for vapor pressure buildup in interstitial space 25 between primary tank wall 20 and secondary tank wall 30 as shown in FIG. 2. A primary emergency vent 80 provides a release for extreme vapor pressure buildup in inner tank volume 120. Manhole 60 is provided to allow inspection of inner tank volume 120 and associated monitoring equipment located inside primary tank 120. Gauge 100 monitors the fuel level in the inner primary tank 120 and fuel inlet 110 functions as a means to pour liquid into the inner primary tank 120.

Sub 1347
[0032] FIG. 3 shows the double wall construction of the present invention in which the interstitial space 25 is filled with insulating material 40 and encased by the outer secondary tank wall 30 and the inner primary tank wall 20. In the preferred embodiment the insulating material 40 is a foam material comprised of synthetic polymer such as polystyrene, urethanes, or polymethyl methacrylate. Fire resistant textile material 50 that is sandwiched between the foam material and the outer secondary tank provides additional fire protection from leakage or penetration of the secondary tank 30. The fire resistant textile material 50 in the preferred embodiment is a high-temperature polyester film material such as Mylar or Kevlar.

[0033] FIG. 4 shows the present invention with a generator and generator housing 140 generally denoted in combination as 130 attached to the top portion of the fuel tank 10. FIG. 5 shows a top view of the tank 10 and generator housing 130. A screened atmospheric vent 105 prevents excessive pressure from building up inside primary tank 120.

[0034] The walls of the double wall tank are made of carbon steel as specified in UL 142 and welded together by conventional techniques well known in the art. In the preferred embodiment, the inner tank is constructed of 1/4 inch A-36 hot rolled carbon steel plate and the outer secondary tank is constructed of 5/16 inch A-36 hot rolled carbon steel plate. The inner tank volume 120 has a nominal capacity of 5500 gallons. The weight of the tank without fuel is approximately 12,500 pounds.

[illegible]

[0036] It is also to be understood that the following claims are intended to cover all of the generic and specific features of the invention herein described, and all statements of the scope of the invention which, as a matter of language, might be said to fall therebetween.

[0037] Now that the invention has been described,